

HUBBARD COMMUNICATIONS OFFICE
Saint Hill Manor, East Grinstead, Sussex

HCO BULLETIN OF 10 DECEMBER 1976RB
RE-REVISED 25 MAY 1980

Remimeo
All Auditors
All Intern
Supervisors
All C/Ses

(This issue is re-revised
to update reference HCOBs
for False TA.)

URGENT—IMPORTANT

C/S Series 99RB

SCIENTOLOGY F/N AND TA POSITION

Through verbal tech just located, it has been found that some auditors have been ordered to disregard all F/Ns that were above 3.0 or below 2.0 on the meter.

Auditors have also called F/Ns which were ARC break needles, thus falsely indicating to the pc.

These two actions—disregarding actual F/Ns because the TA was not between 2.0 and 3.0 and calling “F/Ns” that were actually ARC break needles—have upset many preclears.

The outnesses here are (a) not considering pc indicators as senior and (b) not noting pc indicators when calling an F/N and (c) ignoring and giving junior importance to the technology covered in false TAs. (See list of references at end of this HCOB or the Subject Index of the HCOB Volumes.)

Auditors have even been led to falsify worksheets (giving TA as in range when it actually was not when calling an F/N) because they might “get in trouble” for calling an F/N in the wrong range, such as 1.8 or 3.2.

The CORRECT procedure for out of range F/Ns is

1. Look at the pc's indicators.
2. Call the F/N regardless of its range.
3. Mark down the ACTUAL TA position.
4. Handle the false TA at the earliest opportunity when it will not intrude into the current cycle on which the pc is being audited. (You don't interrupt a Quad R3RA, for instance, to handle false TA; you complete it and then, when directed by the C/S, you handle the false TA.)
5. On any pc you suspect has had his F/Ns disregarded because of false TA, you C/S for and get run a repair and rehab of this error.

E-Meter cans can monitor or change TA position when the palms are too dry or too wet or when the cans are too big or too small or when the wrong hand cream is used. The E-Meter does not read on hand moisture alone as was long believed by people in electronics. But TA depends upon resistance to electrical current in the palms, leads and meter, as well as its main resistance which happens to be mental masses or lack of them.

To simply tell some intern "Always disregard an F/N not in correct range" is to set him up for loses and set the pc up for crashes. The correct information is that an F/N which isn't in range is accompanied by pc indicators that indicate whether it is an F/N or not. AND indicates you better get the false TA handled fast as soon as it won't interrupt the current cycle. AND you always note where it F/Ned so the C/S can C/S for false TA handling.

Where an ARC break needle (which looks like an F/N) is observed, whether it is in range or out of range (2.0 to 3.0 or below 2.0 or above 3.0) you LOOK at the pc and establish the pc's indicators before falsely calling an F/N. A pc who is about to cry is NOT an F/Ning pc and if you indicate an F/N to that pc you will further the ARC break and suppress the emotional charge that is about to come off.

REPAIR

Where the above matters have not been fully understood and errors have occurred on pcs, it must be assumed that

1. Auditors have falsified their worksheets as to TA position and thus built up withholds and made themselves blowy.
2. That every pc who has ever had high or low TA trouble has had F/Ns disregarded and ARC break F/Ns falsely indicated.
3. That a briefing and drilling of all interns and auditors must occur on this HCOB.
4. That a brief program of cleanup of disregarded F/Ns and falsely called ARC break F/Ns be done on every pc.
5. That every such pc be considered as having false TA troubles and these must be C/Sed for and corrected.
6. That all auditors and interns be drilled on all HCOBs relating to pc indicators.

SAMPLE CLEANUP C/S

Disregard TA position, use only F/Ns and pc indicators in doing this C/S.

1. It has been found that some of your F/Ns (release points) may have been disregarded by past or present auditors.
2. Have you ever felt an F/N (release point or end of an action) had been bypassed on your case?
3. Find and rehab the overrun of the release point to F/N. Check for any other bypassed F/Ns and rehab them.
4. Have you ever felt an F/N should not have been indicated by the auditor when it was?
5. Find the point and get in Suppress on it and complete the action. Check "Are there any other F/Ns which should not have been indicated by the auditor when they were?" and handle as above.
6. Find and run the ARC breaks bypassed, with ARC break handling.
7. Find and handle the false TA in totality.

DIANETIC F/Ns

An F/N seen by the auditor in running R3RA is not called until the full Dianetic EP is reached.

An auditor running R3RA is NOT looking for F/Ns. He is looking for the postulate which is sitting at the bottom of the chain he is running.

The EP of a Dianetic chain is always always always the postulate coming off. The postulate is what holds the chain in its place. Release the postulate and the chain blows. That's it.

The auditor must recognize the postulate when the pc gives it, note the VGIs, call the F/N and end off auditing that chain.

An F/N seen as the incident is erasing is not called.

The pc does not have to state that the incident has erased. Once he has given up the postulate, the erasure has occurred. The auditor will see an F/N and VGIs. NOW the F/N is called. F/Ns are not indicated until the EP of postulate off, F/N and VGIs is reached.

It's the postulate—not the F/N—that we are going for in New Era Dianetics.

POWER F/Ns

F/Ns are disregarded in Power.

Each Power Process has its own end phenomena and is ended only when that is obtained.

REFERENCE HCOBs FOR FALSE TA

HCOB 8 Jun 70	LOW TA HANDLING
HCOB 16 Aug 70R	C/S Series 15R, GETTING THE F/N TO THE EXAMINER
HCOB 24 Oct 71RA	FALSE TA
HCOB 12 Nov 71RB	FALSE TA ADDITION
HCOB 15 Feb 72R	FALSE TA ADDITION 2
HCOB 18 Feb 72RA	FALSE TA ADDITION 3
HCOB 16 Feb 72	C/S Series 74, TALKING THE TA DOWN MODIFIED
HCOB 23 Nov 73RB	DRY AND WET HANDS MAKE FALSE TA
HCOB 24 Nov 73RD	C/S 53RL SHORT FORM
HCOB 24 Nov 73RE	C/S 53RL LONG FORM
HCOB 19 Apr 75R	OUT BASICS AND HOW TO GET THEM IN
HCOB 23 Apr 75RA	VANISHING CREAM AND FALSE TA
HCOB 24 Oct 76RA	C/S Series 96RA, DELIVERY REPAIR LISTS
HCOB 10 Dec 76RB	C/S Series 99RB, SCIENTOLOGY F/N AND TA POSITION
HCOB 21 Jan 77RB	FALSE TA CHECKLIST
HCOB 24 Jan 77	TECH CORRECTION ROUND-UP
HCOB 26 Jan 77R	FOOTPLATES USE FORBIDDEN
HCOB 30 Jan 77R	FALSE TA DATA
HCOB 4 Dec 77	CHECKLIST FOR SETTING UP SESSIONS AND AN E-METER

HCOB 13 Jan 77RB HANDLING A FALSE TA
OWNER'S MANUAL, HUBBARD PROFESSIONAL MARK VI,
"HOW TO SET UP YOUR MARK VI E-METER"

PC INDICATORS HCOBs

References:

HCOB 29 Jul 64	GOOD INDICATORS AT LOWER LEVELS
HCOB 28 Dec 63	INDICATORS PART ONE, GOOD INDICATORS
HCOB 23 May 71R VIII Rev. 4.12.74	RECOGNITION OF RIGHTNESS OF THE BEING
HCOB 22 Sep 71	THE THREE GOLDEN RULES OF THE C/S HANDLING AUDITORS
HCOB 21 Oct 68R	FLOATING NEEDLE

L. RON HUBBARD
Founder

Revision assisted by
LRH Technical
Compilations Unit

LRH:RTCU:djm.dd
Copyright © 1976, 1980
by L. Ron Hubbard
ALL RIGHTS RESERVED