

HUBBARD COMMUNICATIONS OFFICE  
Saint Hill Manor, East Grinstead, Sussex

Remimeo

HCO BULLETIN OF 3 JULY 1970

C/S SERIES NO.14

C/Sing 2 WAY COMM

The C/S is liable to make most of his C/S errors in C/Sing 2 way Comm.

The reasons for this are

1. 2 way comm IS auditing.
2. The errors that can be made in any auditing can be made in 2 way comm.
3. Untrained or poorly trained auditors do not always respect 2 way comm as auditing.
4. Errors in 2 way comm become masked since the procedure is loose.
5. Earlier C/Ses on the case may have missed the easily missed 2 way comm errors.

RULES OF C/Sing 2 WAY COMM

A. The C/S must recognize that 2 way comm is auditing. Therefore it follows all the rules of auditing.

B. Any error that occurs in other auditing can occur in 2 way comm auditing. Errors in a 2 way comm session must be carefully looked for as they easily can be masked in the worksheet.

C. Auditors must be persuaded by the C/S to make notation of auditing essentials in 2 way comm as of senior importance to pc's text (which is also made note of in the W/S).

D. The questions asked in 2 way comm can be very incorrect just as rote processes can be.

E. An auditor must be trained as a 2 way comm auditor (Class II). Otherwise he will Evaluate, Q and A and commit other faults.

F. If an ARC break occurs early in a 2 way comm session and is not handled as such the rest of the session is audited over an ARC break and can put a pc into a sad effect.

G. A pc with a FT problem not being handled in the 2 way comm will get no gain.

H. A pc with a w/h in a 2 way comm session will become critical, nattery and/or get a dirty needle.